



DYNAMIC

SIZE	LI&SI	Tread depth (mm)	Speed Range	Pattern	Max Load		Max Pressure	
					KG	LBS	KPA	PSI
165/65 R13	77	7,3	T	DAYNAMIC	412	908	300	44
175/70 R13	82	7,8	H	DAYNAMIC	475	1047	300	44
185/65 R14	86	7,8	H	DAYNAMIC	530	1168	300	44
185/70 R14	88	7,8	H	DAYNAMIC	560	1235	300	44
195/70 R14	91	7,8	H	DAYNAMIC	615	1356	300	44
185/65 R15	91	7,8	H	DAYNAMIC	560	1235	300	44
195/65 R15	91	7,8	H	DAYNAMIC	615	1356	300	44
205/65 R15	91	7,8	H	DAYNAMIC	670	1477	300	44



SUPERWAY

No.	Series	SIZE	Overall Diameter (mm)	Tread depth (mm)	Speed Range	Standard Rim	Load Index	Max Load (Kgs)		Inflation Pressure (Kpa/Psi)
								KGS	LBS	
1	13"	165/65 R13	544	7,8	T	5 J	77	412	908	300/44
2	13"	175/70 R13	576	8	T	5 J	82	475	1047	300/44
3	13"	185/70 R13	590	8	T	5,5 J	86	530	1168	300/44
4	14"	185/65 R14	596	8	H	5,5 J	86	530	1168	300/44
5	14"	185/70 R14	616	8	T	5,5 J	88	560	1235	300/44
6	14"	195/70 R14	630	8	T	6 J	91	615	1356	300/44
7	15"	185/65 R15	621	8	H	5,5 J	88	560	1235	300/44
8	15"	196/60 R15	615	8	V	6 J	88	560	1235	300/44
9	15"	195/65 R15	635	8	HXL	6 J	95	690	1521	340/49
10	15"	205/56 R15	647	8	H	6 J	94	670	1477	300/44
11	16"	205/55 R16	632	8	V	6,5 J	91	615	1356	300/44
12	16"	205/60 R16	642	8	XL	7 J	94	730	1609	340/49
13	17"	205/45 R17	596	8	WXL	7 J	84	560	1235	340/49
14	17"	205/55 R17	606	8	WXL	7 J	95	615	1353	340/49
15	18"	235/60 R18	739	8	HXL	7 J	107	675	1485	340/49
16	18"	245/45 R18	653	8	XL	8,5 J	100	730	1606	340/49



SUPERWAY 1

SIZE	Series	Overall Diameter (mm)	Speed Range	Standard Rim (Inch)	LI&SR	Max Load (Kgs)		Inflation Pressure (Kpa/Psi)
						KGS	LBS	
195 R14	14"	666	C	5.5	106/104R	950	900	8
195 R15	15"	693	C	5.5	106/104R	950	900	8



SUPERWAY 2

SIZE	Series	Overall Diameter (mm)	Speed Range	Standard Rim (Inch)	LI&SR	Max Load (Kgs)		Inflation Pressure (Kpa/Psi)
						KGS	LBS	
225/70 R15	15"	719	ST	6	113/108	1150	1000	8



SIZE	Series	Overall Diameter (mm)	Speed Range	Max Pressure	Standard Rim (Inch)	LI&SR	Max Load (Kgs)		Inflation Pressure (Kpa/Psi)
							KGS	LBS	
205/70 R15	15'	689	S	300	7.5	101/97	1000	2205	6C
285/65 R17	17'	802	H	300	8.5	101/97	1250	2756	6C
285/60 R18	18'	799	H	300	8.5	101/97	1250	2756	6C