

6
Page



PW 01

7
Page



PW228

8
Page



PW279

9
Page



PW281

14
Page



PW582

15
Page



PW624

16
Page



PW625

17
Page



PW626

22
Page



PW977

23
Page



PW988

24
Page



PW400

25
Page



**PW506
PW516**

10
Page



PW298

11
Page



PW395

12
Page



PW580

13
Page



PW581

18
Page



PW758

19
Page



PW800

20
Page



PW801

21
Page



PW899

26
Page



DYNAMIC

27
Page



SUPERWAY

28-30
Page



**SUPERWAY
1/2/3**

31
Page



RIM

CONTANT



SIZE	Ply Rating	Tread depth (mm)	Speed Range	Standard Rim	Load Index	MaxLoad (Kgs)		Inflation Pressure (Kpa)	New Tyre Inflation Dimensions (mm)	
						Single	Double		Overall Diameter	Section Width
6,50 R16	12	9,5	L	5,50F	110/105	1060	925	670	750	185
7,00 R16	14	11	L	5,50F	118/114	1320	1180	750	775	200
7,50 R16	14	12	M	6,00G	122/116	1320	1080	770	805	115
8,25 R16	16	13	M	6,50H	128/124	1800	1600	770	855	135
8,25 R20	16	13	L	6,50	139/137	2450	2300	930	974	136
9,00 R20	16	15,5	L	7,00	144/142	2800	2650	900	1018	159
10,00 R20	18	16,5	L	7,50	149/146	3250	3000	930	1055	278
11,00 R20	18	17	L	8,00	152/149	3550	3250	930	1085	293
12,00 R20	18	17,5	L	8,50	154/151	3750	3450	830	1125	315
12,00 R20	20	17,5	L	8,50	156/153	4000	3650	900	1125	315
12,00 R24	20	16	K	8,50	160/157	4500	4125	900	1226	313
11 R22,5	16	15	M	8,25	146/143	3000	2725	830	1054	279
12 R22,5	16	16,5	M	9,00	152/146	3550	3250	840	1085	300
13 R22,5	18	16,5	L	9,75	154/151	3750	3450	830	1124	320
315/80 R22,5	18	15	K	9,00	154/151	2750	3450	830	1076	312
315/80 R22,5	20	15	K	9,00	156/153	4000	3650	850	1076	312



PW228

SIZE	Ply Rating	Tread depth (mm)	Speed Range	Standard Rim	Load Index	MaxLoad (Kgs)		Inflation Pressure (Kpa)	New Tyre Inflation Dimensions (mm)	
						Single	Double		Overall Diameter	Section Width
1200 R24	18	15,5	K	8,50	158/155	4250	3875	830	1226	313
1200 R24	20	15,5	K	8,50	160/157	4500	4125	900	1226	313



SIZE	Ply Rating	Tread depth (mm)	Speed Range	Standard Rim	Load Index	MaxLoad (Kgs)		Inflation Pressure (Kpa)	New Tyre Inflation Dimensions (mm)	
						Single	Double		Overall Diameter	Section Width
315/80 R22,5	20	15	L	9,00	156/153	4000	3650	900	1076	312



PW281

SIZE	Ply Rating	Tread depth (mm)	Speed Range	Standard Rim	Load Index	MaxLoad (Kgs)		Inflation Pressure (Kpa)	New Tyre Inflation Dimensions (mm)	
						Single	Double		Overall Diameter	Section Width
295/80 R22.5	18	15	L	9,00	152/149	3550	3250	900	1044	298
315/80 R22.5	20	15	K	9,00	154/151	3750	3450	830	1076	312
315/70 R22.5	20	14,5	K	9,00	156/153	4000	3650	850	1076	312



PW298

SIZE	Ply Rating	Tread depth (mm)	Speed Range	Standard Rim	Load Index	MaxLoad (Kgs)		Inflation Pressure (Kpa)	New Tyre Inflation Dimensions (mm)	
						Single	Double		Overall Diameter	Section Width
295/80 R22,5	18	19,5	L	9,00	154/149	3550	3450	900	1044	298
315/80 R22,5	20	19,5	L	9,00	156/153	4000	3650	900	1076	312



PW395

SIZE	Ply Rating	Tread depth (mm)	Speed Range	Standard Rim	Load Index	Max Load (Kgs)		Inflation Pressure (Kpa)	New Tyre Inflation Dimensions (mm)	
						Single	Double		Overall Diameter	Section Width
14,00 R20	18	20	L	10,00	161/158	4625	4250	690	1076	312



PW580

SIZE	Ply Rating	Tread depth (mm)	Speed Range	Standard Rim	Load Index	MaxLoad (Kgs)		Inflation Pressure (Kpa)	New Tyre Inflation Dimensions (mm)	
						Single	Double		Overall Diameter	Section Width
1200 R24	18	16	K	8,50	158/155	4250	3875	830	1226	313
1200 R24	20	16	K	8,50	160/157	4500	4125	900	1226	313
315/80 R22,5	18	16	M	9,00	154/157	3750	3450	830	1076	312
315/80 R22,5	20	16	M	9,00	156/153	4000	3650	850	1076	312



PW581

SIZE	Ply Rating	Tread depth (mm)	Speed Range	Standard Rim	Load Index	MaxLoad (Kgs)		Inflation Pressure (Kpa)	New Tyre Inflation Dimensions (mm)	
						Single	Double		Overall Diameter	Section Width
1200 R24	18	15,5	K	8,50	158/155	4250	3875	830	1226	313
1200 R24	20	15,5	K	8,50	160/157	4500	4125	900	1226	313



PW582

SIZE	Ply Rating	Tread depth (mm)	Speed Range	Standard Rim	Load Index	MaxLoad (Kgs)		Inflation Pressure (Kpa)	New Tyre Inflation Dimensions (mm)	
						Single	Double		Overall Diameter	Section Width
1200 R24	18	16	K	8,50	158/155	4250	3875	830	1226	313
1200 R24	20	16	K	8,50	160/157	4500	4125	900	1226	313



PW624

SIZE	Ply Rating	Tread depth (mm)	Speed Range	Standard Rim	Load Index	Max Load (Kgs)		Inflation Pressure (Kpa)	New Tyre Inflation Dimensions (mm)	
						Single	Double		Overall Diameter	Section Width
7.50R16	14	12	M	6.00G	122/118	1320	1080	770	805	215



PW625

SIZE	Ply Rating	Tread depth (mm)	Speed Range	Standard Rim	Load Index	Max Load (Kgs)		Inflation Pressure (Kpa)	New Tyre Inflation Dimensions (mm)	
						Single	Double		Overall Diameter	Section Width
7.50R16LT	8	12	M	6.00G	122/116	1320	1080	770	805	215



PW626

SIZE	Ply Rating	Tread depth (mm)	Speed Range	Standard Rim	Load Index	Max Load (Kgs)		Inflation Pressure (Kpa)	New Tyre Inflation Dimensions (mm)	
						Single	Double		Overall Diameter	Section Width
7,50R16	14	12	M	6,00G	122/116	1320	1080	770	805	215



PW758

SIZE	Ply Rating	Tread depth (mm)	Speed Range	Standard Rim	Load Index	MaxLoad (Kgs)		Inflation Pressure (Kpa)	New Tyre Inflation Dimensions (mm)	
						Single	Double		Overall Diameter	Section Width
315/80 R22,5	20	20	L	9,00	156/150	4000	3350	900	1076	312



SIZE	Ply Rating	Tread depth (mm)	Speed Range	Standard Rim	Load Index	MaxLoad (Kgs)		Inflation Pressure (Kpa)	New Tyre Inflation Dimensions (mm)	
						Single	Double		Overall Diameter	Section Width
1200 R24	20	24	K	8,50	160/157	4500	4125	900	1226	313



SIZE	Ply Rating	Tread depth (mm)	Speed Range	Standard Rim	Load Index	Max Load (Kgs)		Inflation Pressure (Kpa)	New Tyre Inflation Dimensions (mm)	
						Single	Double		Overall Diameter	Section Width
12,00 R20	20	17,5	L	8,50	156/153	4000	3650	900	1125	315



PW899

SIZE	Ply Rating	Tread depth (mm)	Speed Range	Standard Rim	Load Index	MaxLoad (Kgs)		Inflation Pressure (Kpa)	New Tyre Inflation Dimensions (mm)	
						Single	Double		Overall Diameter	Section Width
385/65 R22,5	20	16	K	11,75	160	4500	4125	900	1072	389



SIZE	Ply Rating	Tread depth (mm)	Speed Range	Standard Rim	Load Index	MaxLoad (Kgs)		Inflation Pressure (Kpa)	New Tyre Inflation Dimensions (mm)	
						Single	Double		Overall Diameter	Section Width
385/65 R22,5	20	16	K	11,75	160	4500	4125	900	1072	389



SIZE	Ply Rating	Tread depth (mm)	Speed Range	Standard Rim	Load Index	Max Load (Kgs)		Inflation Pressure (Kpa)	New Tyre Inflation Dimensions (mm)	
						Single	Double		Overall Diameter	Section Width
385/65 R22,5	20	16	TL	11,75	160 L	4500	4125	900	1072	389



SIZE	Ply Rating	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Load Capacity (kg)	Inflated Pressure (kpa)
1400 20 TT	18	10,00	1215	332	4125	245
1600 20 TT	18	10,00	1330	388	4350	395



PW516
L3/E3



PW506
L3/E3

SIZE	Ply Rating	Tread depth (mm)	Tire Type	Standard Rim	Max Load (Kgs)	Inflation Pressure (Kpa)
15,5 - 25	12	24	TT/TL	12,00	3,250	250
17,5 - 25	16	25	TT/TL	14,00	4,250	300
17,5 - 25	20	25	TT/TL	14,00	4,250	400
20,5 - 25	16	29	TT/TL	17,00	5,450	275
20,5 - 25	20	29	TT/TL	17,00	6,000	325
20,5 - 25	24	29	TT/TL	17,00	6,700	400
23,5 - 25	16	31	TT/TL	19,50	6,150	225
23,5 - 25	20	31	TT/TL	19,50	7,300	300
23,5 - 25	24	31	TT/TL	19,50	8,000	350
26,5 - 25	24	35	TT/TL	22,00	8,250	250
26,5 - 25	28	35	TT/TL	22,00	9,250	300
26,5 - 25	32	35	TT/TL	22,00	10,000	350
29,5 - 25	28	38	TT/TL	25,00	17,500	425



DAYNATIC

SIZE	LI&SI	Tread depth (mm)	Speed Range	Pattern	Max Load		Max Pressure	
					KG	LBS	KPA	PSI
165/65 R13	77	7,3	T	DAYNATIC	412	908	300	44
175/70 R13	82	7,8	H	DAYNATIC	475	1047	300	44
185/65 R14	86	7,8	H	DAYNATIC	530	1168	300	44
185/70 R14	88	7,8	H	DAYNATIC	560	1235	300	44
195/70 R14	91	7,8	H	DAYNATIC	615	1356	300	44
185/65 R15	91	7,8	H	DAYNATIC	560	1235	300	44
195/65 R15	91	7,8	H	DAYNATIC	615	1356	300	44
205/65 R15	91	7,8	H	DAYNATIC	670	1477	300	44



SUPERWAY

No.	Series	SIZE	Overall Diameter (mm)	Tread depth (mm)	Speed Range	Standard Rim	Load Index	Max Load (Kgs)		Inflation Pressure (Kpa/Psi)
								KGS	LBS	
1	13"	165/65 R13	544	7,8	T	5 J	77	412	908	300/44
2	13"	175/70 R13	576	8	T	5 J	82	475	1047	300/44
3	13"	185/70 R13	590	8	T	5,5 J	86	530	1168	300/44
4	14"	185/65 R14	596	8	H	5,5 J	86	530	1168	300/44
5	14"	185/70 R14	616	8	T	5,5 J	88	560	1235	300/44
6	14"	195/70 R14	630	8	T	6 J	91	615	1356	300/44
7	15"	185/65 R15	621	8	H	5,5 J	88	560	1235	300/44
8	15"	196/60 R15	615	8	V	6 J	88	560	1235	300/44
9	15"	195/65 R15	635	8	HXL	6 J	95	690	1521	340/49
10	15"	205/56 R15	647	8	H	6 J	94	670	1477	300/44
11	16"	205/55 R16	632	8	V	6,5 J	91	615	1356	300/44
12	16"	205/60 R16	642	8	XL	7 J	94	730	1609	340/49
13	17"	205/45 R17	596	8	WXL	7 J	84	560	1235	340/49
14	17"	205/55 R17	606	8	WXL	7 J	95	615	1353	340/49
15	18"	235/60 R18	739	8	HXL	7 J	107	675	1485	340/49
16	18"	245/45 R18	653	8	XL	8,5 J	100	730	1606	340/49
17	19"	235/55 R19	763	8	WXL	8	97	1090	2398	340/49



SUPERWAY 1

SIZE	Series	Overall Diameter (mm)	Speed Range	Standard Rim (Inch)	LI&SR	Max Load (Kgs)		Inflation Pressure (Kpa/Psi)
						KGS	LBS	
195 R14	14"	666	C	5,5	106/104R	950	900	8
195 R15	15"	693	C	5,5	106/104R	950	900	8



SUPERWAY 2

SIZE	Series	Overall Diameter (mm)	Speed Range	Standard Rim (Inch)	LI&SR	Max Load (Kgs)		Inflation Pressure (Kpa/Psi)
						KGS	LBS	
225/70 R15	15"	719	ST	6	113/108	1150	1000	8



SUPERWAY 3

SIZE	Series	Overall Diameter (mm)	Speed Range	Max Pressure	Standard Rim (Inch)	LI&SR	Max Load (Kgs)		Inflation Pressure (Kpa/Psi)
							KGS	LBS	
205/70 R15	15"	689	S	300	7,5	101/97	1000	2205	6C
285/65 R17	17"	802	H	300	8,5	101/97	1250	2756	6C
285/60 R18	18"	799	H	300	8,5	101/97	1250	2756	6C